THERMOTEC INVERTER SWIMMING POOL HEAT PUMP

WI-FI MODULE USER MANUAL

FOR ALL VERTICAL AND HORIZONTAL MODELS

(WITH AQUA TEMP APP – AFTER AUG 2020)

FOR WIFI MODULES WITH FOUR LEDS










For Heat Pumps After August 2020 Version 1.0

WIFI Module USER'S MANUAL



Please read this user's manual carefully before use Please keep this user's maunal properly

Thermotec Inverter Wifi Module With Aqua Temp App (From August 2020)



User Privacy Instructions

We take your privacy very seriously and we promise to inform you how we use the data. Users' private data, such as mailboxes, address, before uploading to the cloud, we will get your permission, and we will work hard to protect your data security.

Description

- Receive data signal from cloud server and transmit to the main device;
- Receive data signal from main device and transmit to cloud server;
- To achieve remote upgrade the WIFI module baseplate MCU by cloud server;
- To achieve the remote upgrade of the main device by WIFI module baseplate MCU.

Technical Parameters

OPERATING VOLTAGE: DC8V~12V (Recommended value 12V)

OPERATING CURRENT: Max. recurrent peak 1A, average standby current 50mA

TEMP. RANGE: Operating Temp.: -30 C ~+ 70 C; Storage Temp.: -40 C ~+ 85 C

LED INDICATOR LIGHT:

4 lights, Network configuration indicator, router connection indicator, cloud server connection indicator, 485 communication indicator;


DIMENSION(L×W×H): 78mm×63mm×24mm

Installation

- There is a magnet on the back of the WIFI module, it can be installed indoors or outdoors, and avoid direct sunlight;
- Please scan the following QR code to download APP;



Functional Description



ITEM	NAME	LONG LIGHT	SLOW FLASH	EXTINGUISH
1	Network configuration indicator	Configuring Network	SmartLink configuring	Done
2	Router connection indicator	Normal	Abnormal	
3	Cloud server connection indicator	Normal	Abnormal	
4	485 communication indicator	Normal	Abnormal	

Account Login

Use email address and password to register, login or reset the password.




Fig.2 Account Registration interface

Fig.1 Login interface

Fig.3 Forgot Password interface

1. Account Registration: To register an account, click ① (Fig.1) to jump to the Account Registration interface, fill in the relevant information and click ② to receive verification code, while completed the application information, click ③ to read the details of the Privacy Policy, then click ④ to agree, and click ⑤, registration is done.


Please note, the valid time of one verification code is 15min, please fill in the verification code within 15min, otherwise you need to ask for a new one.

- 2. Log in: Follow the instructions on the page(Fig.1), enter your registered email address and password, click


 (6) and jump to device list;
- 3. Forgot Password: While forget your password, click (7) (Fig.1), jump to the Forgot Password interface (Fig.3). Follow the instructions on the page, fill in the relevant informations, click (3) to receive verification code from your mailbox, click (9) to comfirm and password reset is done.

Add Device

After log in, displays My Device interface (Fig. 4), follow the instruction to add WIFI or DTU.



WIFI Configure Network




- Fig.7 WIFI Module On interface
- Fig.8 Enter password interface

Fig.9 Connect specified WIFI

- 1. Follow the instructions on the page (Fig.7), press button on module and hold for 1s till two lights on, then AP connection is activated, click ①to confrim, click ①to turn the page;
- 2. Click (2) to enter the WIFI password for the current connection, click (3) to confirm;
- 3. Jump to system settings, connect specified WIFI, click (4) to select the "Smart_AP_xxx", click (5) to popup window(Fig.10), follow the instruction and then jump to WIFI setting interface(Fig.11);





- Fig.13 Configure Network interface
- Fig. 14 Bond Device interface

Fig. 15 Scanning interface

- 4. Slide the page back to configure network interface (Fig. 12), click nto join WLAN Network, click to cancel, click 18 to turn next page(Fig. 13); click 19 to bond device (Fig. 14);
- 5. Click "OK" to allow this APP to use the camera for scanning the barcode on heat pump unit (Fig.15); click "OK", device bond is done (Fig.16);
- 6. After WIFI and DTU bonding is done, and jump back to My Device(Fig. 17).



Fig.16 Bond device done interface

Fig.17 Device management interface

Device Management

Device management operations are as below:



Fig. 18 Device Main interface

Fig. 19 The right-hand menu interface






Fig.20 Device Main interface

Fig. 22 Troubleshooting interface

ICON	NAME	FUNCTIONS		
0	ON/ OFF	Click it to turn on/ off the unit		
(1)	Silent Mode Off	Display silent mode off, click it to activate the silent mode		
(I)×	Silent Mode On	Display silent mode on, click it to turn off the silent mode		
	Mode shift	Mode changing: CoolingHeatingAuto		
*	Cooling	Display Cooling mode, click it to change operating mode		
Ø :	Heating	Display Heating mode, click it to change operating mode		
A	Auto	Display Auto mode, click it to change operating mode		
0	Timming settings	Click it to jump to the timer on/ off and mute timer setting interface		
0	Troubleshooting	Click it to jump to the troubleshooting interface		
(a)	Menu	Click to unfold or collapse the menu		

Note:		

Contact details

HeatPumps4Pools Ltd Rosemary Lodge Church Road Ramsden Bellhouse Essex CM11 1RT United Kingdom

Tel +44 1268 206560

www.HeatPumps4Pools.com

enquiries@heatpumps4pools.com



TM



Code 20161227-0003